

**Data Sheet**

Type Number: ..... 6237  
 Designation IEC: ..... ---  
 System: ..... Li-Manganese dioxide /  
 Organic Electrolyte  
 UL Recognition: ..... MH 13654 (N)  
 Nominal Voltage [V]: ..... 3  
 Typical Capacity C [mAh]: ..... 1350

Load 1.0 kOhm, at 20 °C down to 2.0 V

Weight, approx [g]: ..... 15  
 Volume [ccm]: ..... 5,6  
 Coding: ..... Date of Manufacturing  
 Quarter/Year

Temperature Ranges [°C]:  
 min. max.  
 Storage: ..... -55 75  
 Discharge: ..... -30 75

Dimensions [mm]:  
 min. max.  
 Diameter [A]: ..... 14,45 14,75  
 Height [B]: ..... 33,1 33,5  
 Shoulder Diameter[L]: ..... 7  
 Shoulder Height [M]: ..... 0,6

Segment: ..... Electronic

Main Applications: ..... Watch  
 Photo  
 Electronic

**Typical Capacities (at 20° C):**

Discharge Type:	Load	End Voltage:	2.0 V
Continuous	1000	Ω Time:	500 h
24h/d,7d/w		Capacity [mAh]:	1350
Current [µA]:		Energy [mWh]:	3600

