

# Material Safety Data Sheet (MSDS)

For

KEEPPOWER TECHNOLOGY CO., LIMITED 5F, Bldg 4, Fenmenao Industrial Park, Bantian, Long Gang, Shenzhen 518129, China and for their product

#### Protected Li-ion Rechargeable Battery

| Model/type reference         | P1829LT          |
|------------------------------|------------------|
| Trademark                    | KEEPPOWER        |
| Nominal Voltage              | 3.7V             |
| Typical Capacity             | 2900mAh, 10.73Wh |
| Weight                       | 48.0g            |
| Shape and Physical Dimension | H: 69.0mm        |
| (mm):                        | D: 18.5mm        |
| Version number               | V1.0             |
| Preparation Date             | May. 15, 2020    |
| Revision date                | N/A.             |

| Laboratory  | Shenzhen SEM Test Technology Co., Ltd.  |          |  |
|---|---|----------|--|
| Address   | 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd<br>Road, Bao'an District, Shenzhen, P.R.C. (518101) |          |  |
| Compiled by (name+ signature) .:<br>Approved by (name+ signature) | Danica Lin Danta Lin  | <u>.</u> |  |



1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### Product Identifier

Product name: Protected Li-ion Rechargeable Battery Model: P1829LT

#### Other means of identification

Synonyms: none

#### Recommended use of the chemical and restrictions on use

Recommended Use: Used in portable electronic equipments;

Uses advised against:

a) Do not dismantle, open or shred secondary cells or batteries.

b) Do not expose cells or batteries to heat or fire. Avoid storage in direct sunlight.

c) Do not short-circuit a cell or a battery. Do not store cells or batteries haphazardly in a box or

drawer where they may short-circuit each other or be short-circuited by other metal objects.

d) Do not remove a cell or battery from its original packaging until required for use.

e) Do not subject cells or batteries to mechanical shock.

f) In the event of a cell leaking, do not allow the liquid to come in contact with the skin or eyes. If contact has been made, wash the affected area with copious amounts of water and seek medical advice.

g) Do not use any charger other than that specifically provided for use with the equipment.

h) Observe the plus (+) and minus (-) marks on the cell, battery and equipment and ensure correct use.

i) Do not use any cell or battery which is not designed for use with the equipment.

j) Do not mix cells of different manufacturer, capacity, size or type within a device.

k) Battery usage by children should be supervised.

I) Seek medical advice immediately if a cell or a battery has been swallowed.

m) Always purchase the battery recommended by the device manufacturer for the equipment.

n) Keep cells and batteries clean and dry.

o) Wipe the cell or battery terminals with a clean dry cloth if they become dirty.

p) Secondary cells and batteries need to be charged before use. Always use the correct charger and refer to the manufacturer's instructions or equipment manual for proper charging instructions.

q) Do not leave a battery on prolonged charge when not in use.

r) After extended periods of storage, it may be necessary to charge and discharge the cells or batteries several times to obtain maximum performance.

s) Retain the original product literature for future reference.

t) Use only the cell or battery in the application for which it was intended.

u) When possible, remove the battery from the equipment when not in use.

v) Dispose of properly.

#### Details of the supplier of the safety data sheet:

Supplier Name: KEEPPOWER TECHNOLOGY CO., LIMITED

Address: 5F, Bldg 4, Fenmenao Industrial Park, Bantian, Long Gang, Shenzhen 518129, China

Telephone number of the supplier: 0086-755-8995 6056

Emergency Telephone No.(24h): 0086-755-8995 6056

Fax: 0086 -755-8930 9659



1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

E-mail address: info@keeppower.com.cn

#### Emergency telephone number

Company Emergency Phone Number: 0086-755-8995 6056

### 2. HAZARDS IDENTIFICATION

#### Classification = (see section 14)

No harm at the normal use. If contact the Electrolyte liquid in the Protected Li-ion Rechargeable Battery, reference as follows:

#### Classification of the substance or mixture

Classification according to GHS

Acute Toxicity, Oral(Hazard category 4)

Acute Toxicity, Dermal(Hazard category 3)

Skin, irritate(Cagegory 1B)

Eye Irritate (Hazard category 1)

#### GHS Label elements. including precautionary statements:



#### Signal word: Warning

#### Hazard statement(s):

H242:Heating may cause a fire;

H311: Toxic in contact with skin;

H314:Causes severe skin burns and eye damage;

**H302:**Harmful if swallowed;

#### precautionary statements:

#### Prevention:

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

#### Response:

P312:Call a Poison center or doctor/physician if you feel unwell.

P302+P350-IF ON SKIN: Gently wash with plenty of soap and water

P301+P330+P331-IF SWALLOWED: rise mouth. Do NOT induce vomiting

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

#### Storage:

None

#### Disposal

**P501:** Dispose of contents/container in accordance with local/national regulations

#### Hazards not otherwise classified (HNOC)

Not Applicable

#### Other information



Road, Bao'an District, Shenzhen, P.R.C. (518101)

No information available.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Chemical characterixation: Mixtures

#### **Description:**

Product: Consisting of the following components.

| Common Chemical Name                                    | Concentration (%) | CAS Number                              | EC No.                 |
|---|-------------------|---|------------------------|
| Lithium transition metal oxidate(Li[M]m[O]n *2)         | 20-35             | 12190-79-3<br>12057-17-9<br>182442-95-1 | 235-362-0              |
| Iron  | 15-25             | 7439-89-6                               | 231-096-4              |
| Aluminum  | 2-6               | 7429-90-5                               | 231-072-3              |
| Copper  | 5-15              | 7440-50-8                               | 231-159-6              |
| Graphite<br>(Natural graphite)<br>(Artificial graphite) | 10-20             | 7782-42-5<br>7440-44-0                  | 231-955-3<br>231-153-3 |
| Organic electrolyte                                     | 10-20             | N/A                                     |                        |

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

# 4. FIRST-AIDMEASURES

#### First aid measures

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Swallowing Do not induce vomiting. Get medical attention.

Most Important Symptoms/Effects No information available.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically

# 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

CO2, dry chemical powder, water spray.



1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

Unsuitable Extinguishing Media: No information available.

#### Specific Hazards Arising from the Chemical

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide(CO)

Carbon dioxide

Other irritating and toxic gases.

#### **Hazardous Combustion Products**

Carbon oxides.

**Explosion Data** 

Sensitivity to Mechanical Impact No

Sensitivity to Static Discharge No

#### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

#### Special hazards arising from the substance or mixture:

Battery may burst and release hazardus decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150°C), When damaged or abused(e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions. protective equipment and emergency procedures

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

#### **Environmental precautions**

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

#### Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling



1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Wash thoroughly after handling. Use this material with adequate ventilation. The product is not explosive.

#### Conditions for safe storage. including any incompatibilities

If the Protected Li-ion Rechargeable Battery is subject to storage for such a long term as more than 3 months, it is recommended to recharge the Protected Li-ion Rechargeable Battery periodically. 3 months:  $-10^{\circ}C \sim +40^{\circ}C$ , 45 to 85%RH

And recommended at  $0^{\circ}C \rightarrow +35^{\circ}C$  for long period storage.

The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more.

The voltage for a long time storage shall be 3.0V~4.2V range.

Do not storage Protected Li-ion Rechargeable Battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.

Keep out of reach of children.

Do not expose Protected Li-ion Rechargeable Battery to heat or fire. Avoid storage in direct sunlight. Do not store together with oxidizing and acidic materials.

Keep ignition sources away- Do not smoke.

Store in cool, dry and well-ventilated place.

Incompatible Products None known.

# 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### **Control parameters**

| Ingredients with limit values that require monitoring at the workplace: |                       |  |  |
|---|-----------------------|--|--|
| 12190-79-3 Lithium Cobalt Oxide   |                       |  |  |
| TLV (USA)   | 0.02mg/m <sup>3</sup> |  |  |
| MAK (Germany)   | 0.1mg/m <sup>3</sup>  |  |  |

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962(11th Cir., 1992).

#### Appropriate engineering controls

Engineering Measures Showers

Eyewash stations

Ventilation systems

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Ensure adequate ventilation.

Individual protection measures. such as personal protective equipment Eye/Face Protection:



Tightly sealed goggles Body protection: Protective work clothing. Skin protection:





### Protective gloves

#### Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material:

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Respiratory Protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

|  | Form: Cylindrical              |                               |  |  |
|--|--------------------------------|-------------------------------|--|--|
| Physical                                     | Color: Black                   |                               |  |  |
| State  | te Odour: Odourless            |                               |  |  |
|  | Odor Threshold: No information | available                     |  |  |
| Change in                                    | condition:                     |                               |  |  |
| pH, with inc                                 | lication of the concentration  | Not determined.               |  |  |
| Melting poin                                 | nt/freezing point              | Not determined.               |  |  |
| Initial boilin                               | g point and Boiling range:     | Not determined.               |  |  |
| Flash Point                                  |                                | Not determined.               |  |  |
| Evaporation rate                             |                                | Not determined.               |  |  |
| Flammability (solid, gas)                    |                                | Not determined.               |  |  |
| Upper/lower flammability or explosive limits |                                | Not determined.               |  |  |
| Vapor Pressure:                              |                                | Not determined.               |  |  |
| Vapor Density:                               |                                | Not determined.               |  |  |
| relative density:                            |                                | Not determined.               |  |  |
| Solubility in Water:                         |                                | Not determined.               |  |  |
| Solubility in other solvents                 |                                | Not determined.               |  |  |
| n-octanol/water partition coefficient        |                                | Not determined.               |  |  |
| Auto-ignitio                                 | n temperature                  | Product is not self-igniting. |  |  |

### 9. PHYSICAL AND CHEMICAL PROPERTIES



1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

Material Safety Data Sheet

| Decomposition temperature | Not determined.                            |
|---------------------------|--|
| Odout threshold           | Not determined.                            |
| Evaporation rate          | Not determined.                            |
| Viscosity                 | Not determined.                            |
| Other Information         | No further relevant information available. |

# 10. STABILITY AND REACTIVITY

**<u>Reactivity</u>**: Stable under recommended storage and handling conditions (see section 7, Handling and storage).

<u>Chemical stability:</u> Stable under normal conditions of use, storage and transport.

**Thermal decomposition/conditions to be avoided:** No decomposition if used according to specifications.

Possibility of Hazardous Reactions: None under normal processing.

Hazardous Polymerization: Hazardous polymerization does not occur.

**<u>Conditions to avoid:</u>** Strong heating, fire, Incompatible materials.

Incompatible materials: Strong oxidizing agents. Strong acids.Base metals.

Hazardous Decomposition Products: Carbon oxides, Other irritating and toxic gases.

### **11. TOXICOLOGICAL INFORMATION**

Acute toxiciy: No data available.

LD/LC50 values relevant for classification:

Not available.

Skin corrosion/irritation: No irritant effect.

Serious eye damage/irritation: Cause serious eye irritation.

Respiratory or skin sensitization: No sensitizing effects known.

Specific target organ system toxicity: No information available.

**CMR effects(carcinogenity, mutagenicity and toxicity for reproduction):** No information available.

### 12. Ecological Information

#### Toxicity:

Acquatic toxicity:

No further relevant information available.

**Persistence and degradability:** No further relevant information available.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment



Road, Bao'an District, Shenzhen, P.R.C. (518101)

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects: No information available.

# 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Recommendation: Must not be disposed together with household garbage.

Do not allow product to reach sewage system

#### Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

# 14. TRANSPORT INFORMATION

The dangerous goods regulations require that each battery design be subject to tests contained in Section 38.3 of UN Manual of Tests and Critical prior to being offered for transportation.

The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

UN number : UN3480 or UN3481;

UN Proper shipping name/Description (technical name): Lithium ion batteries or Lithium ion batteries contained in equipment or Lithium ion batteries packed with equipment;

UN Classification (Transport hazard class): Class 9 dangerous goods;

When the following requirements are met, can be shipped without being declared as Class 9 dangerous goods:

1: Shipped by air meets the requirement of Packing Instructions PI965, PI966 and PI967 Section II appropriate of IATA Dangerous Goods Regulations 61<sup>st</sup> Edition(IATA DGR 61<sup>st</sup>) for transportation;

2: Shipped by sea meets the requirement of Special Provision 188 appropriate of International Maritime Dangerous Good Code (IMDG CODE 39-18) for transportation;

3: Shipped by road meets the requirement of Special Provision 188 appropriate of International Carriage of Dangerous Goods by Road (ADR 2020) for transportation;

4: Shipped by rail meets the requirement of Special Provision 188 appropriate of International Carriage of Dangerous Goods by Rail (RID 2020) for transportation;

# **15. REGULATORY INFORMATION**

Safety. health and environmental regulations/legislation specific for the substance or mixture EU Regulation:

Authorisations: No information available.



1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

#### Restrictions on use: No information available. Regulatory information

| CAS No.     | EU         | US         | Japan      | Canada     | Australia  | Korea      | China      |
|-------------|------------|------------|------------|------------|------------|------------|------------|
|             | (EINECS)   | (TSCA)     | (ENCS)     | (DSL/      | (AICS)     | (ECL)      | (IECSC)    |
|             |            |            |            | NDSL)      |            |            |            |
| 12190-79-3  | Listed     | Not listed | Not listed | NDSL       | Not listed | Not listed | Not listed |
| 7439-89-6   | Listed     | Listed     | Listed     | DSL        | Listed     | Listed     | Listed     |
| 7429-90-5   | Listed     | Listed     | Listed     | DSL        | Listed     | Listed     | Listed     |
| 7440-50-8   | Not listed | Listed     | Not listed | DSL        | Listed     | Listed     | Listed     |
| 7782-42-5   | Not listed | Listed     | Not listed | DSL        | Listed     | Listed     | Listed     |
| 7440-44-0   | Listed     | Listed     | Listed     | DSL        | Listed     | Listed     | Listed     |
| 12057-17-9  | Listed     | Not listed | Not listed | Not listed | Not listed | Not listed | Listed     |
| 182442-95-1 | Listed     | Listed     | Not listed | NDSL       | Not listed | Not listed | Not listed |

#### Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

#### Transportation regulations

IATA Dangerous Goods Regulations 61st Edition(IATA DGR 61st), effective January 1,2020 International Maritime Dangerous Good Code (IMDG CODE 39-18), effective January 1,2020 International Carriage of Dangerous Goods by Road (ADR 2020), effective January 1,2020 International Carriage of Dangerous Goods by Rail (RID 2020), effective January 1,2020

### **16. OTHER INFORMATION**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Reference:

ISO 11014:2009 Safety data sheet for chemical products-Content and order of sections

GB/T 16483-2008 Safety data sheet for chemical products-Content and order of sections

#### Relevant phrases:

R20/22: Harmful by inhalation and if swallowed.

R36: Irritating to eyes.

H302: Harmful if swallowed.

H332: Harmful if inhaled.